



ITEM \ SIZE	2.5	3	3.5	4	4.5	5	6
DK	4.50-5.00	5.50-6.00	6.40-7.00	7.40-8.00	8.40-9.00	9.40-10.0	11.3-12.0
K1	1.19-1.35	1.44-1.64	1.69-1.99	1.95-2.25	2.17-2.57	2.46-2.86	2.94-3.44
K2	0.93-1.10	1.04-1.44	1.29-1.65	1.51-1.87	1.70-2.06	1.92-2.28	2.76-3.33
h (MAX)	0.40	0.50	0.60		0.80		1.00
d1	2.30-2.50	2.75-3.00	3.2-3.50	3.7-4.00	4.2-4.50	4.70-5.00	5.70-6.00
d2	1.40-1.60	1.70-1.90	2.00-2.20	2.30-2.50	2.50-2.70	2.70-3.00	3.30-3.60
p \approx	1.1	1.35	1.6	1.8	2.0	2.2	2.6
a (MAX)	1.1	1.35	1.6	1.8	2.0	2.2	2.6
NO.	1		2				3
	m \approx	2.6	3.0	4.0	4.4	4.8	5.3
	t	1.25-1.50	1.60-2.01	1.76-2.06	2.05-2.51	2.46-2.92	2.99-3.45
	0.05-0.18			0.10-0.23			
HVO.3	560-800						
EHVO.3	320-420						
M \geq	1	1.5	2	3.0	4.3	6.2	10.8
\geq	15°						
C1022							
L	Lo		L			Lo	
	Min	Max		Min	Max		
10	9.1	10	73MM	40	38.75	40	C1022
12	11.1	12		45	43.75	45	
13	12.1	13		50	48.75	50	
15	14.1	15		60	58.5	60	
16	15.1	16		70	68.5	70	
18	17.1	18		80	78.5	80	
20	18.95	20		90	88.25	90	
25	23.95	25		100	98.25	100	
30	28.95	30		110	108.25	110	
35	33.75	35		120	118.25	120	

				EX-002B	
				2017-09-23	
					Material
					C1022