(E DECLAF	RATION OF PERF	ORMANCE	
		2 305 - 0004 1/11/2015 -UK		
1.	Unique identification code of the product-type:			
	Scala 55 Connect PUR, Scala 30 Connect PUR			
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):			
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specifi- cation, as foreseen by the manufacturer:			
	For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.			
	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):			
	DLW Flooring GmbH, Stuttgarter Str. 75, 74321 Bietigheim-Bissingen			
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):			
	Nicht zutreffend			
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:			
	System 3			
	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant			
			not applicable	
	TFI notifizierten Nr.1658 Notified Body		certificate of constancy of performance	
	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not applicable			
	Declared performance			
[Essential characteristics	Performance	Harmonised technical specification	
	Reaction to fire	B _{II} -s1	EN 14041: 2004/AC:2006	
	Content of Pentachlorophenol	DL PCP	EN 14041: 2004/AC:2006	
	Formaldehyd Emissions	ÑA HCHO	EN 14041: 2004/AC:2006	
	Slip resistance	CAR DS	EN 14041: 2004/AC:2006	
	Electrical behavior (dissipative)	NPD	EN 14041: 2004/AC:2006	
	Electrical behavior (conductive)	NPD	EN 14041: 2004/AC:2006	
	Electrical behavior (antistatic)	NPD	EN 14041: 2004/AC:2006	
	Thermal conductivity [W/mK]	0,25 W / mK	EN 14041: 2004/AC:2006	
	Water-tightness	NPD	EN 14041: 2004/AC:2006	
	The performance of the product identified in points 1 and 2 This declaration of performance is issued under the sole r Signed for and on behalf of the manufacturer by:			
	Remco Veeneman / CEO		A	
	(name and function)		Ah .	
	Bietigheim-Bissingen, 1.11.2015		4	
	(place and date of issue)		(signature)	