



PURA® NFC

| | | |
|---|--|---|
| Unique identification code of the product-type | PURA® NFC | |
| Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer | Compact laminate panels for external wall finish Type EDF according to EN438 part 6 | |
| Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) | TRESPA International B.V. Wetering 20 / NL – 6002 SM Weert | |
| System or systems of AVCP (=assessment and verification of constancy of performance) | System 1 | |
| Name and identification number of the notified body | NB 0958 / SGS INTRON Certificatie B.V NB 1173 / WFRGENT N.V. | |
| Declared performance | | |
| Essential characteristics | Performance | Harmonized technical specification |
| Reaction to fire | B-s2,d0 | EN 438 – 7:2005 |
| Fire Resistance | NPD | |
| Water vapour permeability | NPD | |
| Resistance to fixings | ≥ 3.000 N | |
| Direct airborne sound insulation | NPD | |
| Flexural strength | ≥ 120 MPa | |
| Flexural modulus | ≥ 9000 MPa | |
| Thermal resistance / conductivity | NPD | |
| Resistance to climatic shock | Appearance ≥ 4 Ds ≥ 0.80 / Dm ≥ 0.80 | |
| Durability: Resistance to wet conditions | Mass Increase ≤ 3 % Appearance surface rating ≥ 4 Appearance edge rating ≥ 3 | |
| Density | ≥ 1,35 g/cm ³ | |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

J.A.L. Horbach (CEO)

Weert, The Netherlands, October, 2020